

# StormTight LED

## Specifications: StormTight LED Modules

Color	Product #	LED/ Module	L	Size W	D	VHB Double Sided Tape	Volts	Modules per 60W	Modules per 120W	Modules/ Foot	Modules/ Box	Watts/ Module	Viewing Angle
High Output White	ACLW-WHO	1	1.54"	1.42"	0.45"	NO	12VDC	45	90	2	20	1.0	110°
Designer Series White	ACLW-5CW2 -D	2	2"	0.5"	0.125"	YES	12VDC	90	180	2	30	0.48	110°
Designer Series White (Single)	ACLW-5CW1 -D	1	1"	0.5"	0.125"	YES	12VDC	180	360	4	60	0.24	110°
Classic Series White	ACLW-mCW2	4	2"	0.5"	0.125"	YES	12VDC	90	180	2	30	0.72	110°
Twin White	ACLW-5CW2	2	2"	0.5"	0.125"	YES	12VDC	75	150	2	25	0.84	110°
Red	ACLW-mR2	4	2"	0.5"	0.125"	YES	12VDC	90	180	2	30	0.72	110°
Blue	ACLW-mB2	4	2"	0.5"	0.125"	YES	12VDC	90	180	2	30	0.72	110°
Yellow	ACLW-mY2	4	2"	0.5"	0.125"	YES	12VDC	90	180	2	30	0.72	110°
Green	ACLW-mG2	4	2"	0.5"	0.125"	YES	12VDC	90	180	2	30	0.72	110°
Orange	ACLW-mO2	4	2"	0.5"	0.125"	YES	12VDC	90	180	2	30	0.72	110°

"Allanson LED. The Future is Now."

LED@allanson.com | 1.800.668.9162  
www.allansonLED.com

