



# Allanson

## StormTight II



### ACLW-CW2-LP

- Innovative design for shallow channel letters
- Works in applications as shallow as 2 ½ inches
- Wide 155° viewing angle
- Easy installation with single mounting hole and double sided tape
- Sealed fire resistant construction for reliable, all weather operation and durability
- High density plastic, one piece design for greater outdoor protection
- Metal back housing promotes cooler temperature and long life operation
- White 6700°K

StormTight II

MODULES NOV-2011

StormTightLED



ENERGY SAVINGS

LOOK FOR THIS MARK  
SIGNIFYING ENERGY SAVING PRODUCTS  
FROM ALLANSON

# StormTight II

Specifications	
Part number	ACLW-CW2-LP
Dimensions LxWxH	1.771in x 0.748in x 0.189in
LEDs per Module	2
Lumens per Module	39
Watts per Module	0.48
Lumens per Watt	81
Modules per Foot	3
Lumens per Foot	117
Supply Voltage	DC 12V
Power capacity	100 modules per CV125-120 power supply
Packaging	100 modules per tray 12 trays per carton

Compatible Power Supplies		Modules per Power Supply (Max Load)
CV121	(12W)	18
CV125	(60W)	100
CV125-120	(60W)	100
CV12125	(2 X 60W)	200



## US

**Phone:** 1-800-559-3659

**Fax:** 1-615-643-1890

**Email:** [customerservice@eballast.com](mailto:customerservice@eballast.com)

## CANADA

**Phone:** 1-800-661-7251

**Fax:** 1-416-752-6717

**Email:** [custserv@allanson.com](mailto:custserv@allanson.com)

For all your population services contact us at:

[led@allanson.com](mailto:led@allanson.com)

Visit Us at: [www.allansonled.com](http://www.allansonled.com)