



Allanson

StormTight II



ACLW-CW2-LP

- Innovative design for shallow channel letters
- Works in applications as shallow as 2 1/2 inches
- Wide 155° viewing angle
- Easy installation with single mounting hole and double sided tape
- Sealed fire resistant construction for reliable, all weather operation and durability
- High density plastic, one piece design for greater outdoor protection
- Metal back housing promotes cooler temperature and long life operation
- White 6500°K

StormTight II

MODULES NOV-2011

StormTightLED



ENERGY SAVINGS



LOOK FOR THIS MARK
SIGNIFYING ENERGY SAVING
PRODUCTS FROM ALLANSON

StormTight II

Specifications	
Part number	ACLW-CW2-LP
Dimensions LxWxH	1.771in x 0.748in x 0.189in
LEDs per Module	2
Lumens per Module	39
Watts per Module	0.48
Lumens per Watt	81
Modules per Foot	3
Lumens per Foot	117
Supply Voltage	DC 12V
Power capacity	112 modules per CV125-120 power supply
Packaging	100 modules per tray 12 trays per carton

Compatible Power Supplies		Modules per Power Supply (Max Load)
CV121	(12W)	22
CV122-12	(12W)	45
CV125	(60W)	112
CV125-120	(60W)	112
CV12125	(2 X 60W)	224



US

Phone: 1-800-559-3659

Fax: 1-615-855-0592

Email: customerservice@eballast.com

CANADA

Phone: 1-800-661-7251

Fax: 1-416-752-6717

Email: cservice@allanson.com

For all your population services contact us at:

led@allanson.com

Visit us at: www.allansonled.com